

MATERIAL SAFETY DATA SHEET

TRADE NAME: Basic Oxygen Furnace Slag SYNONYMS: BOF Slag; "SF"; Steel Slag

I. PRODUCT AND COMPONENT DATA

Component(s):	CAS Registry% (Approx.)	ACGIH TLV-TWA
Steel Furnace Slag	65996-71-6 100	None Known

Composition of BOF Slag Range

SiO ₂ :	10 - 23%
Al ₂ O ₃ :	0 - 13%
CaO:	22 - 53%
MgO:	6 - 13%
MnO:	0 - 8%
FeO:	20 - 56%
S:	0 - 2%

* Composition Varies due to the many different types of steel manufactured, the exact chemistry of BOF/SF slag may vary. Composition consists primarily of silicates and alumino-silicates of calcium plus lime-iron compounds and free lime.

II. PHYSICAL DATA

SOLUBILITY: Negligible FLASH POINT: NA

SPECIFIC GRAVITY: 3.0 - 3.5 FLAMMABLE LIMITS: NA

APPEARANCE & ODOR: Dark gray, vesicular stony material; no distinctive odor.

INCOMPATIBILITY: None known

STABILITY/REACTIVITY: Unweathered BOF/SF slag may contain potentially expansive compounds.

III. PERSONAL PROTECTION AND CONTROLS

RESPIRATORY: If airborne concentrations exceed recommended exposure limits, a suitable NIOSH/MSHA approved filter respirator should be worn. General ventilation or local exhaust is normally adequate to control dust emissions, if not engineering controls should be utilized.

EYE: Safety glasses with side shields should be worn as minimum protection from impact. Dust goggles should be worn when excessively dusty conditions are present or anticipated.

GENERAL: The use of hard hats and hard toed shoes is recommended. Gloves may be worn to protect from abrasion.

IV. FIRST AID

INHALATION: Remove to fresh air. *

SKIN: Wash with soap and water.

EYE: Flush with water immediately for 15 minutes. *

* If irritation is aggravated or persists, contact a physician.

V. HEALTH HAZARDS

EXPOSURE LIMITS: ACGIH TLV's
Total Dust: 10mg/M3 < 1% quartz
Respirable dust: 5mg/M3 < 1% quartz

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:
Exposure to dust may cause irritation to the skin, eyes, or respiratory system or may aggravate existing skin, eye, or respiratory system disease.

ROUTE OF EXPOSURE: Inhalation

ACUTE TOXICITY: Exposure to dust may irritate the respiratory system, eyes, or skin.

CHRONIC TOXICITY: Steel furnace slag is not listed on the NTP, IARC, or OSHA lists of carcinogens.

VI. STORAGE AND SPECIAL PRECAUTIONS

Respirable dust may be generated during processing, handling, and storage. Use personal protective equipment as noted in Section III.

VII. SPILL, LEAK, AND DISPOSAL METHODS

Pick up mechanically or by hand tools and reuse or dispose of as a common non-hazardous material in accordance with applicable Federal, State, and local laws. Use personal protective equipment as described in Section III.

VIII. TRANSPORTATION

DOT Hazard Classification and placard not required. Some areas require the use of tarps on trucks for containment of dust.

IX. ADDITIONAL INFORMATION

Contact: Edw. C. Levy Co. Business phone: 313-429-2200
8800 Dix Ave.
Detroit, MI 48209

This product contains the following EPCRA Section 313 chemical subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372):

<u>CAS#</u>	<u>Chemical Name</u>	<u>Percent by Weight</u>
NA	Manganese Compounds	3-8%

X. DATE ISSUED

ISSUED: May 2009 **SUPERCEDES:** May 2002

DISCLAIMER:

The data supplied in this Material Safety Data Sheet is, to the best of our knowledge and belief, accurate and reliable. The Levy Company does not warrant or guarantee their accuracy or reliability, and will not be liable for any loss or damage arising out of the use thereof. The information contained herein is offered for the user's consideration, examination, and determination of suitability.